FUJITSU

DATA SHEET

LIFEBOOK E8420

The expert without compromises

Issue: October 2009

LIFEBOOK E8420

The simple philosophy behind LIFEBOOK E8420: only the best is good enough. It is the ideal choice for performance-oriented office-based users: use state-of-the-art technology and work becomes a pleasure. 39.1 cm (15.4-inch) WSXGA+ display and an optional NVIDIA graphics card ensure a brilliant display screen and best performance.

More than enough performance

Maximum productivity even for the most demanding of applications thanks to state-of-the-art technology.

- Intel® Centrino® 2 with vPro™ technology, optional high-performance NVIDIA graphics card

Ideal substitute for a desktop

Effective working even for the most demanding of users in all situations.

- 39.1cm (15.4-inch) WSXGA+ display, modular bay, optional second 320GB hard disk drive

Maximum connectivity

Be available wherever you are; wireless connectivity anytime anywhere, even if there is no hotspot nearby.

- Optional integrated 3G/UMTS, WLAN and Bluetooth

Maximum security

Protect your company data against unauthorized third-party access.

- Benefit from our end-to-end anti-theft concept with system and user protection, such as Computrace® enabled BIOS and Advanced Theft Proetection, optional fingerprint sensor, TPM module and SmartCase Logon+

Great flexibility

The family concept offers standard accessory components for the LIFEBOOK Series.

- Standardized port replicator, power supply unit and modular bay for optical drive, second battery or second hard disk drive

intel CORE 2 vPro inside

SIERRA WIRELESS EMPOWERED

ENERGY STAR

Green IT

BEST CONNECTIVITY

SYSTEM GUARDS

ULTIMATE SECURITY

FAMILY CONCEPT

2ND BATTERY

BRILLIANT GRAPHICS

FULL SET OF INTERFACES

INFORMATION DISPLAY

CONFCAM

Components

Processor	Intel® Core™2 Duo processor T9600 (2.8 GHz, 6 MB, 1066 MHz)
	Intel® Core™2 Duo processor P8800 (2.66 GHz, 3 MB, 1066 MHz)
	Intel® Core™2 Duo processor P8700 (2.53 GHz, 3 MB, 1066 MHz)
Memory modules	2 GB (1 module(s) with 2 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM
	1 GB (1 module(s) with 1 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM
Hard disk drives (internal)	320 GB, 5400 rpm, SATA, 2.5-inch S.M.A.R.T.
	320 GB, 5400 rpm, FDE, 2.5-inch S.M.A.R.T.
	160 GB, 7200 rpm, SATA, 2.5-inch S.M.A.R.T.
	160 GB, 5400 rpm, SATA, 2.5-inch S.M.A.R.T.
	160 GB, 5400 rpm, FDE-3, 2.5-inch S.M.A.R.T.
Hard disk notes	ShockSensor for HDD shock protection One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software
Display	39.1 cm (15.4-inch) TFT 1680 x 1050 pixel (WSXGA+) non-glare display
	39.1 cm (15.4-inch) TFT 1280 x 800 pixel (WXGA) non-glare display (Intel® graphics)
WLAN (optional)	Atheros Minicard b/g 802.11 b/g
	Intel® Wireless WiFi Link 5300 AGN 11/13ch
UMTS/HSUPA (optional)	Sierra Wireless MC8790 (downlink 7.2 MBit/s, uplink 2.0 MBit/s)
Bluetooth (optional)	Bluetooth 2.1
Modular bay options	2nd battery
	2nd hard disk drive
	DVD Super Multi
	Weight saver

Base unit	**LIFEBOOK E8420 NVIDIA gfx**	**LIFEBOOK E8420 Intel gfx**
General system information		
Chipset	Intel® PM45, ICH 9-ME	Intel® GM45, ICH 9-ME
BIOS features	BIOS based on Phoenix SecureCore	BIOS based on Phoenix SecureCore
Memory slots	2 DIMM (DDR3)	2 DIMM (DDR3)
Turbo memory	Optional 4 GB	Optional 4 GB
Supported capacity RAM (min.)	1 GB	1 GB
Supported capacity RAM (max.)	4 GB	4 GB
Memory notes	8 GB - with future memory modules.	8 GB - with future memory modules.
Interfaces		
Memory card slots	1	1 (SD/MS/MSPro)
ExpressCard slots	1	1
PC Card slot (Type I/II)	1	1
SmartCard slot	1	1
SIM card slot	1	1
Modem (RJ-11)	1 (optional)	1 (optional)
USB 2.0 total	4	4
FireWire (IEEE1394)	1	1
Serial (RS-232)	1	1
Parallel	1	1
VGA	1	1
HDMI	1	1
Ethernet (RJ-45)	1	1
DC-in	1	1
Audio: line-in / microphone	1	1
Audio: line-out / headphone	1	1
Internal microphones	2	2
Docking connector for Port Replicator	1	1

Interfaces		
Kensington Lock support	2	2
Wired communication		
Modem type	Optional: 56 K V.92 modem MDC1.5	Optional: 56 K V.92 modem MDC1.5
LAN	Built-in 10/100/1000 MBit/s Intel® 82567LM	10/100/1000 MBit/s Intel® 82567LM
Wireless technologies		
Antennas	3 Dual band WLAN antennas, 2 UMTS antenna	3 Dual band WLAN antennas, 2 UMTS antenna
Infrared link (Fast IrDa 1.1, 4 Mbps)	1	1
WLAN notes	Import and usage according to country-specific regulations.	Import and usage according to country-specific regulations.
Keyboard and pointing devices		
	Spillproof keyboard	Spillproof keyboard
	Number of keyboard keys: 86, Keyboard pitch: 19 mm, Keyboard stroke: 2.7 mm	Number of keyboard keys: 86, Keyboard pitch: 19 mm, Keyboard stroke: 2.7 mm
	TouchStick TouchPad with two mouse buttons and one scroll button Second set of mouse buttons EcoButton LockWorkstation button MobilityCenter button Optional: Fingerprint sensor	TouchStick TouchPad with two mouse buttons and one scroll button Second set of mouse buttons EcoButton LockWorkstation button MobilityCenter button Optional: Fingerprint sensor
Multimedia		
Audio type	On board	On board
Audio codec	Realtek ALC269	Realtek ALC269
Audio features	Stereo speakers, 2 internal microphones	Stereo speakers, 2 internal microphones
Camera	Optional: Built-in webcam, 1.3 megapixel, VGA camera	Optional: Built-in webcam, 1.3 megapixel, VGA camera
Graphics		
Max. resolution external display	1920 x 1200 pixel	1920 x 1200 / true color / 60 Hz
Graphics brand name	NVIDIA® GeForce® 9300M GS	Intel® GMA 4500
Graphic features	DualView (Windows XP & Windows Vista)	DualView (Windows XP & Windows Vista)
Power supply		
AC adapter	19 V / 100 W (5.27 A)	19 V / 80 W (4.22 A)
Rated voltage range	100 - 240 V (AC Input)	100 - 240 V (AC Input)
Rated frequency range	50 - 60 Hz	50 - 60 Hz
1st battery	Li-Ion battery 8-cell, 5200 mAh, 74 Wh	Li-Ion battery 8-cell, 5200 mAh, 74 Wh
2nd battery (optional)	Li-Ion, 3800 mAh, 41 Wh	Li-Ion, 3800 mAh, 41 Wh
Battery features	Dynamic charge supported (rapid charge)	Dynamic charge supported (rapid charge)
Benchmark	Mobile Mark 2005	Mobile Mark 2005
Runtime 1st battery	up to 5 h	up to 7 h
Runtime 1st + 2nd battery	up to 7:45 h	up to 11 h
Battery notes	Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.	Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.
Power consumption		
Power consumption note	see white paper Energy Consumption	
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=ba456383-5387-4df1-ac75-f6baf24a6e03	
Dimensions / Weight / Environmental		
Dimension (W x D x H)	357 x 260 x 36 mm	357 x 260 x 36 mm
Weight	2.7 kg	2.7 kg
Weight notes	Weight may vary depending on actual configuration	Weight may vary depending on actual configuration
Operating ambient temperature	5 - 35°C	5 - 35°C

Dimensions / Weight / Environmental		
Operating relative humidity	20 - 85 % (running)	20 - 85 % (running)
Operating system		
Operating system optional preinstalled	Microsoft® Windows Vista® Business 32bit Microsoft® Windows Vista® Home Basic TwinLoad Microsoft® Windows® XP Professional (DVD)	Microsoft® Windows Vista® Business 32bit Microsoft® Windows Vista® Home Basic TwinLoad Microsoft® Windows® XP Professional (DVD)
Operating system compatible	Microsoft® Windows® XP Professional	Microsoft® Windows® XP Professional
Operating system notes	Driver support for Microsoft Windows XP	Driver support for Microsoft Windows XP
Additional Software		
Additional software (preinstalled)	Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Wireless Selector Utility EasyGuide online user documentation Nero Essentials S (CD / DVD write software) Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Toshiba Stack 4.x	Adobe Acrobat Reader Application Panel Display Manager ShockSensor Utility Power Saving Utility Wireless Selector Utility EasyGuide online user documentation Nero Essentials S (CD / DVD write software) Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP Toshiba Stack 4.x
Additional software (optional)	Windows Vista® recovery media Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) SmartCase Logon+	Windows Vista® recovery media Drivers & Utilities DVD (DUDVD) UMTS connection manager (optional with UMTS) SmartCase Logon+
Manageability		
Manageability features	DeskUpdate Driver management DeskView Migrate (optional) DeskView Control (optional)	DeskUpdate Driver management DeskView Migrate (optional) DeskView Control (optional)
Manageability type	DeskView 10.x client management including:	DeskView 10.x client management including:
DeskView features	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)
Supported standards	WMI PXE BootP (made4you)	WMI PXE BootP (made4you)
Manageability link	http://ts.fujitsu.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html	http://ts.fujitsu.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html
Security		
Physical security	Kensington Lock support	Kensington Lock support
System security	Advanced Theft Protection Computrace® enabled BIOS Optional: Trusted platform module (TPM 1.2) Symantec Norton Internet Security (90 day test version)	Advanced Theft Protection Computrace® enabled BIOS Optional: Trusted platform module (TPM 1.2) Symantec Norton Internet Security (90 day test version)
User security	Optional: Integrated Fingerprint Sensor Integrated SmartCard controller in PC Card with system lock support Separate SmartCard slot Hard disk password SystemLock BIOS SmartCard security User and supervisor BIOS password	Integrated Fingerprint Sensor Integrated SmartCard controller in PC Card with system lock support Separate SmartCard slot Hard disk password SystemLock BIOS SmartCard security User and supervisor BIOS password

Compliance	
Europe	CE CE!
USA/Canada	FCC Class B (depending on wireless configuration) CSA cUL UL
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronical equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) WiFi certified ENERGY STAR® 4.0 EPEAT® Silver
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

Portreplicator interfaces (optional)	
DC-in	1
Power on switch	1
Headphones	1
Audio: microphone in	1
USB 2.0 total	4
VGA	1
DVI	1 (with HDCP Support)
Serial (RS-232)	1
Mouse / Keyboard (PS/2)	1
Ethernet (RJ-45)	1
Parallel	1
Kensington Lock support	2

Warranty	
Standard Warranty	2 years
Service level	Collect & Return Service / Bring-In Service (depending on country)

Maintenance and Support Services - the perfect extension	
Recommended Service	3 years, On-site Service
Spare Parts availability	5 years
Service Weblink	htttp://ts.fujitsu.com/Supportservice

Information about environmental care, policies, programs and our Environmental Guideline FSC 03230:
http://ts.fujitsu.com/aboutus
Take back and Recycling information:
http://ts.fujitsu.com/recycling

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions October 2009

Published by
Fujitsu Technology Solutions
http://ts.fujitsu.com